

APU-RS16i

Rack-mount protection unit

DATASHEET V1.3

amina

Product Description

16-channel passive rack-mounted protection unit for Amina Invisible Loudspeakers. For use in installations with higher numbers of low-impedance speakers with a centralised AV rack. Direct-to-PCB screw terminal-blocks allow for fast and easy permanent installation.

Each channel of protection contains a resettable thermal fuse which can be independently set to protect different models of Amina Invisible Loudspeakers, meaning that a single unit can protect a whole system, no matter which speakers have been specified. Removing the top panel of the unit reveals jumper-leads for each channel, enabling fast and secure setup. Please refer to table below for protection configuration.

Default setting set to 15W to ensure protection of lowest power speakers out of the box. Please note that protection setting will need to be changed to ensure maximum performance of the connected loudspeaker.

Not suitable for high impedance 100V/70V line installations.



Example Applications

Installations with large number of speakers and a centralised rack to provide secure and neat protection of Amina Invisible Loudspeakers.

Compatible Loudspeakers

Amina Mobius, Evolution, iQ Developer Series Invisible Loudspeakers.

Please note that repeated tripping of thermal fuse will affect the trip-point, resulting in reduced maximum power handling before protection kicks in. Protection may be replaced to restore full performance.

Protection Group

1	iQ1, iQ2 (dual-channel)
3	AlW350iN, AlW350iN-S200, AlW450iN (dual-channel), iQ3
5	AlW550iN
7	Mobius7, AlW750iN

Compatible Loudspeakers

Specifications

Electrical connection	Direct-to-PCB screw terminal blocks
Dimensions	1U high, front panel 482mm x 44.4mm (19" x 1 3/4"), case depth 213mm (8 3/8")
Product weight	3.14Kg (6lbs 14oz)
Speaker families protected	Mobius, Evolution, iQ
Default protection setting	APUi10 - 15W

APU-RS16i

Distribuidor em Portugal da Amina Technologies Limited
SISLITE - Rua Sá de Figueiredo 6 - C, 2790-233 Carnaxide
T: 21 417 76 21 | E: geral.sislite@sislite.pt | W: www.sislite.pt