

Backbox CV200

Cavity Wall Backbox

DATASHEET V2.0

amina

Product Description

The BackboxCV200 is an easy to install mounting option in plasterboard cavity walls (drywall) for Amina Invisible Loudspeakers with the dimensions 200mm x 450mm (AIW350iN-S200, AIW750iN-HF).

The Backbox CV200 creates an acoustically tuned and consistent cavity behind the speaker, helping to ensure both consistent audio quality as well as minimising rearward airborne sound transmission.



Installation

Designed to be retrofitted into a 12.5mm plasterboard wall or ceiling, the Backbox CV200 provides a consistent mounting platform to achieve correct loudspeaker alignment. The backbox should only make contact with the rear of the plasterboard and not touch the stud framework, this is to minimise the likelihood of mechanical noise transmission from the speaker into the structure of the building.

Please refer to the installation manual for full fitting details, including options for mounting speakers with shim kits into double-skinned plasterboard, or where board has a thickness other than 12.5mm.

Sound Absorption Characteristics

When used with an Amina Invisible Loudspeaker, the BackboxCV200 offers an amount of airbourne noise transmission reduction. With an average attenuation of 26dB between 150Hz-20KHz, the BackboxCV200 is the easiest way of mechanically fixing the loudspeaker to the plasterboard whilst also limiting rearward airborne transmission and helping to achieve consistent loudspeaker performance.

It is recommended that additional steps are taken to reduce rearward transmission if speakers are to be located in partition walls, or will back onto an adjacent occupied room (bedrooms above living spaces etc). For further information about reducing rearward transmission, please contact Amina technical support.

Specifications

Dimensions

Plasterboard cut-out required

Weight

Speaker cable entry

Speaker fixing

Wall fixing

Minimum cavity depth

Sound pressure attenuation

BackboxCV200

500mm x 206mm x 71.5mm
(19^{11/16}" x 8^{2/16}" x 2^{13/16}")

455mm x 205mm

1.2Kg (2.64lbs)

Rubber grommet (can be replaced by M20 gland)

4x self tapping flange-head screws (supplied)

8x self tapping drywall screws (supplied)

75mm

-26dB on average over 150Hz - 5kHz range

Amina Technologies Limited

Cirrus House, Glebe Road, Huntingdon, Cambridgeshire, PE29 7DL, England

T: +44 (0) 1480 354390 | E: inspired@amina.co.uk | W: www.amina.co.uk

DISTRIBUIDOR EM PORTUGAL



R. Sá de Figueiredo 6 - C
2790-233 Carnaxide
Telef. (+351) 21 417 76 21 ♦ Fax. (+351) 21 030 00 31
Web: www.sislite.pt - email: geral.sislite@sislite.pt