smartCUE-one

IP Interface

Main Features

- Wired 10/100 BaseT LAN communication
- Control ports - bi-directional serial and digital I/O
- Power over Ethernet (PoE) power supply
- Front panel indicators for each control port
- Web server and Admin Web pages for setup
- Fully compatible with CUE's mobile solution, touch panels and controllers
- Fully compatible with Cue Visual Composer software
- Unified aluminium enclosure

Description

Ultra-compact interface smartCUE-one allows to control devices from a controller or touch panel over an Ethernet network. Using this unit the number of control ports can be cost-effectively expanded. Additionally it simplifies control of equipment located at an extended distances from a controller.

Applications

- Commercial single-room applications
- Commercial huge multi-room and multi-floor distributed systems
- Home theater applications
- Complete residential home automation

Specifications

Control ports
- 1x Bi-directional serial RS-232
  - Baud rate from 300 to 460 800 bps
  - 5-pin connector
- 8x Digital I/O
  - Digital input
  - Digital open collector output max. 80 mA
  - 2x 5-pin connector with common ground

LED indicators
- Power, Ethernet link, Control ports

Button
- Set factory default

Software technologies
- Integrated web server for setup

Communication
- Wired 10/100 BaseT Ethernet , RJ-45 connector

Power supply
- Power over Ethernet (PoE)
- IEEE 802.3af Class 1 compatible

Physical
- Aluminium enclosure
- Dimensions 105 x 43.5 x 92 mm / 4.14" x 1.7" x 3.6"
- 1/4 rack space, 1 U
- Weight 0.3 kg / 0.7 lb

Environment conditions
- Operating temperature 10° to 40° C
- Storage temperature 0° to 60° C
- Relative humidity 10% to 90% non-condensing

Front Panel



Rear Panel



Order Information

Product code CS0440

Box Contents

Interface smartCUE-one
Connector set
Ethernet cable straight-through
CE Declaration, RoHS Declaration
Data Sheet, Cue System Connector Wiring Sheet

DISTRIBUIDOR EM PORTUGAL

SISLITE
Integração de Sistemas

R. Sá de Figueiredo 6 – C
2790-233 Carnaxide
Telef. (+351) 21 417 76 21 ◆ Fax. (+351) 21 030 00 31
Web: www.sislite.pt - email: geral.sislite@sislite.pt