

TECHNICAL SPECIFICATIONS

Model Name	HA200
Product Type	Headphone Amplifier
Connections - Input	RCA, XLR
Connections - Output	XLR, 6.3 mm
Connections - Control	N/A
Power Output	393mW @ 16 Ohm 747mW @ 32 Ohm 383mW @ 100 Ohm 129mW @ 300 Ohm 70mW @ 600 Ohm
Peak Output Power	600mW @ 16 Ohm 937mW @ 32 Ohm 530mW @ 100 Ohm 180mW @ 300 Ohm 96.3mW @ 600 Ohm
Input Impedance	22k Ohm
Output Impedance	5 Ohm
Nominal Input Level	0.5V
Recommended Headphone Impedance	32 –600 Ohm
Balanced Mode	200 Ohm, 14.6Vrms
Gain	10dB
Frequency Response	10Hz - 20KHz
Sensitivity	0.5V
Signal to Noise Ratio (SNR)	>106dB
Total Harmonic Distortion + Noise (THD + N)	0.0005%
Power Supply	115V/230V
Power Consumption	22W

PHYSICAL SPECIFICATIONS

Weight	5.06 lb (2.2 kg)
Dimensions (W x D x H)	9" x 8.5" x 1.7" (217 x 231 x 44 mm)
Color	Black

ADDITIONAL INFORMATION

Standard Accessories	Power cord x1 Manual x1
Warranty	2-Year
UPC	816924 01 1011



DISTRIBUIDOR EM PORTUGAL



R. Sá de Figueiredo 6 – C
2790-233 Carnaxide
Telef. (+351) 21 417 76 21 ♦ Fax. (+351) 21 030 00 31
Web: www.sislite.pt - email: geral.sislite@sislite.pt